

Explore the next generation of Midmark® sterilizers

Designed for better:

- DURABILITY
- WORKFLOW
- EFFICIENCY



Increase Longevity

25,000 CYCLES
Gain 2.5-times longer device life than previous models.

Reduce Lifetime Cost*

UP TO \$2,180 SAVINGS PER YEAR
Save thousands per year thanks to Steam Flush Pressure Pulse technology that eliminates the need for HEPA filters and daily Bowie-Dick testing.

**\$7 per Bowie-Dick test x 260 working days (\$1820) + \$180 HEPA filters twice a year (\$360) = \$2,180

[LEARN MORE](#)

Enhance Workflow



3 LANGUAGES
Select English, French or Spanish for your preferred display language.**

**French and Spanish available with a future software update



LIGHTER, LARGER TRAYS
More usable space with a larger but lighter tray than previous models.



5-INCH TOUCHSCREEN
Navigate setup with a clear, graphical display you can utilize while wearing gloves.

Improve Efficiency

AUDIO + VISUAL INDICATORS

Determine cycle status—cycle in progress, cycle complete and cycle error—from a distance with a progressing color-coded LED light bar, large cycle-countdown clock and audible cues.

[DISCOVER](#)



CYCLE IN PROGRESS

CYCLE COMPLETE

CYCLE ERROR



TIME-SAVING DOCUMENTATION
Help save time, simplify staff training and build instrument processing confidence with automated mechanical monitoring and chemical indicator reporting.



OPTIONAL AUTOFILL + AUTO-DRAIN
Get fresh water for every cycle without burdening your team.

Reduce Stress



ONSCREEN GUIDANCE
Improve safety with touchscreen prompts that lead your team through a standardized process.



ON-DEVICE TUTORIALS
Reduce the burden of training with step-by-step tutorials.



STREAMLINED RECORDKEEPING
Stay informed with device reminders and notifications, user authentication, unlimited storage of routine care events for the life of the sterilizer, and automated cycle recordkeeping.

[LEARN MORE](#)



ROBUST CYCLE OPTIONS

Preset and custom cycle options help simplify clinical workflow to accommodate unique instrument instructions for use (IFUs).



WRAPPED
270°F, 4 MIN

NEW



WRAPPED
275°F, 3 MIN



DELICATE
250°F, 30 MIN



UNWRAPPED
270°F, 3 MIN



5 CUSTOM CYCLES***
250°F–275°F, 3 MIN–45 MIN

***These cycles are not FDA-cleared, and validation of the sterility of items processed using a custom cycle is the responsibility of the user.

Create a safer practice with technology designed to simplify instrument processing and support an efficient standard of care.

